

Dialog DataStar[options](#)[logoff](#)[feedback](#)[help](#)[databases](#)[search
page](#)[titles](#)

Document

Select the documents you wish to save or order by clicking the box next to the document, or click the link above the document to order directly.

[save](#)

locally as: PDF document

☐ include search strategy[next
document](#)[order](#)☐ document 1 of 2 [Order Document](#)**INSPEC - 1969 to date (INZZ)****Accession number & update**

6117498, C9902-7460-024; 981215.

Title

Control and dynamics simulation facility at Hughes Space and Communications.

Author(s)[Zammit-S.](#)**Author affiliation**

Hughes Space & Commun Co, El Segundo, CA, USA.

Source

Proceedings of AIAA Modeling and Simulation Technologies Conference, New Orleans, LA, USA, 11-13 Aug. 1997.

In: p.442-8, 1997.

ISSN

ISBN: 1-56347-236-8.

Publication year

1997.

Language

EN.

Publication type

CPP Conference Paper.

Treatment codes

T Theoretical or Mathematical.

Abstract

For spacecraft which involve complex attitude or payload control subsystems, and in addition, complex mission operations, a hardware-in-the-loop (HIL) simulation environment is shown to be an essential and cost effective technique for developing and validating mission software, procedures and operations, and is an essential tool for on-orbit problem diagnosis. This paper presents a case history of the application of HIL simulation to the mission development of the Hughes HS601 family of body-stabilized geosynchronous communications satellites. By integrating the HIL simulation, used in the development, qualification and acceptance testing of the attitude control subsystem, with a real-time, digital simulation of the remaining non-ACS spacecraft subsystems (power, thermal, propulsion, telemetry and command, and payload), a comprehensive, high fidelity spacecraft simulator was developed which incorporated critical flight attitude control electronics hardware and software. The simulator system architecture is reviewed, describing applications of this system to ground station software development and its use for validation and mission operations procedure development and evaluation are discussed. The use of the simulator for real-time mission rehearsals, with the simulator linked to the actual mission ground station is described. Planned use of the system for mission support and on-orbit

anomaly investigations is reviewed. (1 refs).

Descriptors

aerospace-simulation; artificial-satellites; attitude-control; control-engineering-computing;
digital-simulation; dynamics.

Keywords

control simulation facility; dynamics simulation facility; Hughes Space and Communications; attitude control subsystems; payload control subsystems; hardware in the loop simulation environment; HIL simulation; Hughes HS601 body stabilized geosynchronous communications satellites; attitude control subsystem; real time digital simulation; nonACS spacecraft subsystems; critical flight attitude control electronics; ground station software development; mission ground station; on orbit anomaly investigations; mission support.

Classification codes

C7460 (Aerospace engineering computing).
C3360L (Aerospace control).
C7420 (Control engineering computing).
C3120C (Spatial variables control).

Copyright statement

Copyright 1998, IEE.

COPYRIGHT BY Inst. of Electrical Engineers, Stevenage, UK

locally as: ☐ include search strategy

Top - News & FAQs - Dialog

© 2003 Dialog